

INCH-POUND

MIL-P-642/13B
AMENDMENT 1
10 July 1997

MILITARY SPECIFICATION SHEET

PLUGS, TELEPHONE (TYPE PJ-777, PJ-778) 3 CONDUCTOR, SINGLE, DOUBLE

This amendment forms a part of MIL-P-642/13B, dated 31 October 1988, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1: Delete ".545" and substitute ".550 MAX".

FIGURE 1: Delete ".143" and ".065".

FIGURE 1: Add a new dimension, ".688 \pm .010", extending from the left edge of the deleted .143 dimension to the right edge of the .550 MAX dimension.

NOTE: New dimension is the same as the sum of the original .545 and .143 dimensions and their tolerances.

FIGURE 1: Delete ".500 \pm .010" and substitute ".490 MIN".

PAGE 2

FIGURE 2: Delete ".520" and substitute ".550 MAX".

NOTE: The left leader line of this dimension points to the intersection of the ramp and the .150 \pm .002 diameter cylinder. This intersection is not necessarily the juncture of the dielectric and the outer conductor barrel.

FIGURE 2: Delete ".497" and substitute ".490 MIN".

Custodians:

Army - CR
Navy - EC
Air Force - 85

Preparing activity:

DLA - CC

(Project 5935-4031)

Review activities:

Army - AR, AV, ME, MI
Navy - AS, MC, SH, YD
Air Force - 19, 99

AMSC/NA

1 of 1

FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.